

KENCO ENGINEERING COMPANY

REPAIR KITS FOR MODEL K9900

GAUGE GLASS REPAIR KIT

K9900-RK-(CENTERLINE)-(O-RING SEAL MATERIAL)*
GLASS LENGTH = CENTER/CENTER – 3/4”

*IF YOU REQUIRE SPECIAL GLASS [I.E. REDLINE (-RL), STANDARD GLASS WITH REDLINE TAPE (-GSRL), HIGH PRESSURE (-HP), HIGH PRESSURE GLASS WITH REDLINE TAPE (-HPRL), HEAVY WALL (-HW), HEAVY WALL GLASS WITH REDLINE TAPE (-HWRL)], THE CORRESPONDING SUFFIX FOR THE REQUIRED GLASS TYPE MUST BE ADDED TO THE END OF THE GAUGE GLASS REPAIR KIT PART NUMBER. (EXAMPLE K9900-RK-24-T-HP)

CONSISTS OF:

- (1) 5/8” O.D. GAUGE GLASS
- (2) O-RING SEALS

O-RING SEAL OPTIONS

V=FLUOROCARBON

A=AFLAS

B=BUNA-N

E=ETHYLENE PROPYLENE

T=PTFE ENCAPSULATED SILICONE

VALVE STEM PACKING REPAIR KIT

K9900-VK

CONSISTS OF:

- (2) VALVE STEMS
- (2) RETAINER WASHER FOR VALVE STEM PACKINGS
- (4) VALVE STEM PACKINGS

REPLACEMENT SHIELD REPAIR KIT

3725-SI-(SHIELD STYLE)-(LENGTH OF SHIELD)

SHIELD LENGTH = GAUGE CENTER TO CENTER – 1 3/8”

STANDARD SHIELD STYLES:

L = CLEAR POLYCARBONATE

L-UV = CLEAR UV FILTERED ACRYLIC

M = EXPANDED METAL

RH = RATE / HEIGHT SCALE

MRH = METRIC RATE / HEIGHT SCALE

H = HEIGHT SCALE

MH= METRIC HEIGHT SCALE

* TO ENSURE CALIBRATION ACCURACY, RATE SCALES(-RH, -MRH) SHOULD ONLY BE SELECTED WITH THE -GS AND -GSRL GLASS OPTIONS

O-RING REPAIR KIT

(REPLACES ALL O-RINGS)

K9900-OK-(O-RING SEAL MATERIAL)

CONSISTS OF:

(2) GAUGE GLASS SIGHT TUBE O-RING SEALS

(2) MISALIGNMENT UNION O-RING SEALS

(4) TEFLON VALVE STEM PACKINGS